



## Displaying of up to 75 channels (up to 2250 fps)

### NMS Client Station

### NMS CLIENT 7-T



#### Brief

- Monitoring of up to 120 channels
- Display of up to 75 channels (up to 2250 fps)
- Supports resolution up to 2592 x 1944
- Supports up to 6 monitors simultaneously
- Quick start up due to the system SSD
- Operating system: Microsoft Windows Embedded 8
- Recording and surveillance system: NMS (Novus Management System)
- Compatible with all NMS Network Video Recorders

#### Software



#### VIDEO

IP Cameras	120 channels at 1280 x 720 resolution (video + audio)
Supported Cameras/Protocols	NOVUS, RTSP
Supported Resolution	max. 2592 x 1944
Monitor Output	main (split screen, full screen, sequence): 2 x HDMI, 4 x DVI, 2 x Display Port (up to 6 monitors simultaneously)*
Dualstreaming Support	yes

#### AUDIO

Audio Output	1 x line-out (Jack 3.5 mm) 2 x HDMI 1 x S/PDIF (optical)
--------------	--

#### DISPLAY

Display Speed	2250 fps (75 x 30 fps for 1280 x 720)** 1800 fps (60 x 30 fps for 1920 x 1080)** 900 fps (9 x 15 fps for 2048 x 1536)** 720 fps (60 x 12 fps for 2592 x 1944)**
---------------	---

#### PLAYBACK

Playback Speed	480 fps (16 x 30 fps for 1280 x 720) 300 fps (10 x 30 fps for 1920 x 1080) 135 fps (9 x 15 fps for 2048 x 1536) 108 fps (9 x 12 fps for 2592 x 1944)
----------------	---

Recorded Data Search	by date/time, events, "Text-in"
----------------------	---------------------------------

BACKUP	
Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	AVI, NMS
STORAGE	
Internal storage for system	built-in: 1 x SSD 2,5" SATA
NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s
Network Protocols Support	HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DNS, NTP, RTSP, UPnP, SMTP
PC/MAC Software	NMS, Internet Explorer/-
Bandwidth	250 Mb/s in total from all NVRs
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands, patterns, tours, auto-scans***
AUXILIARY INTERFACES	
USB Ports	6 x USB 2.0, 4 x USB 3.0
OPERATING SYSTEM	
Operating System	Microsoft Windows Embedded 8
Recording and Surveillance System	NMS (Novus Management System)
Operation Mode	triplex
OSD	languages: Polish, English, Russian, others
Control	PC mouse and keyboard (in-set included), network, DCZ keyboard
System Diagnostic	automatic control of: HDDs, network, camera connection loss
Security	password protection, IP filtering, limiting the number of connections
INSTALLATION PARAMETERS	
Dimensions (mm)	205 (W) x 442 (H) x 540 (D)
Weight	10 kg
Power Supply/Power Consumption	built-in PSU 230 VAC/700 W
Operating Temperature	5°C ~ 35°C

*\* To support more than four monitors it is required to use Display Port output. \*\* Available with dual streaming mode. \*\*\* Function capability depends on used devices and communication protocols.*



442 mm



205 mm



540 mm

