

Switch 8 port PoE+ NV-108S/P+



Features

- 8 x 100 Mb/s
- 2 x UPLINK Gigabit: Ethernet 1000 Mb/s, SFP
- IEEE802.3 at PoE+

Specifications	Description
Transmission Distance	10/100 port: 150m UPLINK port: 100m PoE+ 1-8: 20m PoE 1-8: 150m
Key Buttons	8 reset buttons, one for each interface 1 switch reset button
PoE Protocol	IEEE802.3 af, IEEE802.3 at
Surge protection	Yes
Power Efficiency for 1-8 ports	110 W for all ports, up to 30 W for one port
MAC Address List	8 K
Package Data Cache	1 MB
External Ports	10/100 port: 10/100 Mbps PoE network port UPLINK port: 10/100/1000 Mbps network port SFP: 1000Mbps optical fiber SFP module port
Network Standard	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/LX
Power Supply	48 VDC - 57 VDC PSU in-set included
Power Consumption	< 5 W
Operating Temperature	-10°C ~ 55°C
Dimensions (mm)	159 (W) x 46.5 (H) x 110 (D)
Weight	570 g