

Day/Night Classic Camera NVDN-402C



Features

- Mechanical IR cut filter
- Horizontal resolution up to: 700 TVL
- \bullet Min. Illumination: from 0.005 lx/F=1.2
- Wide Dynamic Range (WDR) for enhanced image quality in diverse light conditions
- Digital Noise Reduction (DNR)
- High Light Compensation (HLC)
- Privacy zones: 4
- Other functions: various picture effects, motion detection
- OSD menu, available:
- Locally directly from the camera
- Remote by coaxial cable using remote controller NC-RCUTC (optional)
- Power supply: 12 VDC

Specifications	Description
Pick-up Element	1/3" SONY Super HAD II CCD imager
Number of effective pixels	976 (H) x 582 (V)
Horizontal Resolution	650 TVL - color mode, 700 TVL - B/W mode
Min. Illumination	0.05 lx/F=1.2 - color mode (1/50 s), 0.005 lx/F=1.2 - B/W mode (1/50 s)
S/N Ratio	More than 52 dB
Electronic Shutter	Auto: 1/50 s ~ 1/100 000 s
Auto Gain Control (AGC)	On/Off
Wide Dynamic Range (WDR)	On/Off
White Balance	7 modes: Manual/ ATW/Push/Indoor/ Outdoor/Anti CR/Push Lock
Back Light Compensation (BLC)	On/Off
Synchronization	Internal
Day/Night Switching	Auto/manual
Filter Delay	0-255 s
Iris Mode	D
Lens Mount	C/CS
Video Output	1.0 Vp-p/75 Ohm (BNC)
Set-up	Multi-lingual On Screen Display (OSD)
Privacy Zones	4
Other Functions	Digital Noise Reduction (DNR), High Light Compensation (HLC), Motion detection, Various picture effects: Mirror image, Image sharpness adjustment
Power Supply	12 VDC
Power Consumption	0.9 W

DAY/NIGHT CAMERA

\$650



Specifications	Description
Operating Temperature	-30°C ~ 45°C
Dimensions (mm)	58 (W) x 62 (H) x 128 (L)
Weight	370 g