

Surge Protector NVS-021VPS



| Specifications | Description |
|--|--|
| Device Type | Power and Video 2 in 1 Surge Protector |
| Video Continuous Operating Voltage | 5 V |
| Video Max. Operating Voltage | 6 V |
| Video Nominal Discharging Current (8/20μs) | 5 kA |
| Video Max. Discharging Current (8/20μs) | 10 kA |
| Video Limit Voltage (10/700μs) | < 20 V |
| Video Response Time | ≤ 1 ns |
| Video Insertion Loss | ≤ 0.5 dB |
| Video Insertion Impedence | ≤ 1Ω |
| Video Bandwidth | 10 MHz |
| Power Continuous Operating Voltage | 24 V |
| Power Max. Operating Voltage | 36 V |
| Power Nominal Discharging Current (8/20μs) | 5 kA |
| Power Max. Discharging Current (8/20μs) | 10 kA |
| Power Limit Voltage | < 200 V (8/20μs) |
| Power Rated Overload Current | ≤ 10 A |
| Power Leakage Current | ≤ 5 μA |
| Power Response Time | ≤ 25 ns |
| Case | Aluminium, black |
| Operating Temperature | -20 ~ 55°C |
| Dimensions (mm) | 112 (L) x 63 (W) x 38 (H) |
| Weight | 172 g |