


Confidea CV

WIRELESS CHAIRMAN VOTING UNIT

Art. 71.98.0012



Description

The Confidea wireless unit combines a slim, contemporary design, excellent intelligibility and ease of use with a robust and reliable wireless connection which sets it apart from traditional wireless systems.

It allows the chairman of a conference to speak, request-to-speak, listen to the speaker and vote

The units are equipped with a microphone On/ Off or request-to-speak button, two headphone outputs with a single volume control and three voting buttons with a voting result information display.



To guide the meeting in an easy way the chairman has the ability to use its priority, next-in-line; system volume adjustment and voting session control buttons.



In a stand-alone configuration of an access point (Confidea WCAP) and several delegate units (Confidea DV) basic voting sessions can be performed without the need of a central control unit. The voting session is controlled via the chairman voting control buttons, the results of the session are displayed on the OLED information display of each unit within the system.

Battery management is crucial using a wireless conference system. Therefore Confidea units combine a smart power management with an easy to replace removeable Lithium-ion battery pack. This results in a controllable and flexible recharging schedule. (Confidea BP, to be ordered separately)

A screw lock connector is provided to connect a removable microphone which is immune against GSM disturbances (MIC 38SL, to be ordered separately).

To prevent eavesdropping and unauthorized access, the Confidea® wireless system and the discussion units have a digital encryption mechanism to keep information of the meeting confidential.

Controls and Features

- Three voting buttons
- OLED voting result display
- Built-in high quality loudspeaker which is automatically muted when the microphone is active, to prevent acoustic feedback.
- Microphone On/Off or request-to-speak button with two signalling LEDs
- Two headphone outputs
- One headphone volume adjustment

Status Control

• Red battery status LED

4 h remaining : 1 Hz blinking 2h remaining : 2 Hz blinking 1h remaining : 4 Hz blinking

Blue link status LED

Off: connection established Blinking: low link quality

 Blue link status LED + Microphone LED Blinking: out of range, shutdown after 2

min.

Connectivity

- Two 3.5 mm jack plugs for headphones
- Battery pack connection
- Screw lock socket to connect removable microphone

Specifications

Technical Data		
Audio quality	16 bit digital	
Headphone load impedance	> 32 ohm < 1k ohm	
Output power	16.5 mW / 32 ohm	
Power Supply	Battery pack	
Dimensions	230(w), 130(h), 60(d)	
Weight (g)	450	
Color	RAL9011	
Part number	Confidea CV 71.98.0012	

Accessories

•	Removeable microphone MIC38SL	71.98.0050
•	Battery pack Confidea BP	71.98.0042
•	Transport case Confidea CHC	71.98.0044
•	Headphones TEL151	71.04.0151