

## Color Megapixel Dome IP Camera with Electronic Day/Night Function

NVIP-2C2001D-P/GO



### Features

- Electronic day/night function
- Imager: 3.0 MPX CMOS, 1/2.8" SONY
- Camera resolution: 2.0 MPX (Full HD)
- Min. Illumination: 0.63 lx/F=2.0
- Digital Slow Shutter (DSS)
- Digital Noise Reduction (DNR)
- Automatic Defective Pixel Correction (DPC)
- Standard lens: f=2.1 mm
- 3-axis camera module adjustment
- Built-in webserver: video compression and real-time network transmission
- Compression: H.264 or M-JPEG
- Video processing resolution: 1920 x 1080 Full HD
- Dual streaming: compression, resolution, speed and quality defined individually for two video streams
- RTP/RTSP protocol support for video transmission
- Hardware motion detection
- PoE (Power over Ethernet) support

Specifications	Description
Pick-up Element	1/2.8" SONY 3.0 MPX CMOS imager, progressive scanning
Camera Resolution	2.0 MPX (Full HD)
Min. Illumination	0.63 lx/F=2.0 - color mode 0.63 lx/F=2.0 - B/W mode
S/N Ratio	> 50 dB (AGC Off)
Electronic Shutter	Auto/Manual (1/4 ~ 1/2 000 s)
Digital Slow Shutter (DSS)	x2
White Balance	Manual/ATW
Day/Night Switching	Auto
Lens type	Standard: f=2.1 mm
Angle of View (H)	128°
Image Functions	Automatic DPC (Defective Pixel Correction)
Video Output	1.0 Vp-p/75 Ohm (BNC)
Video Compression	H.264/M-JPEG
Resolution	1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 704 x 576, 640 x 480, 352 x 288
System Reaction to Alarm Events	E-mail with attachment, saving file on FTP
Frame Rate	Up to 30 fps for 1920 x 1080 and lower resolution
Image Saving Files	JPEG

Specifications	Description
Video streaming	2 streams
External Ports	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Motion Detection	Hardware
Time Synchronization	Automatic time synchronization with NTP server
Network Protocols Support	HTTP, TCP/IP, UDP, FTP, DHCP, NTP, RTSP, RTP, UPnP
User Authorization	Password protected camera access and its configuration
Power Supply	PoE (IEEE 802.3af)
Power Consumption	3.3 W
Operating Temperature	-10°C ~ 50°C
Dimensions (mm)	110 (Ø) x 67.5 (H)
Weight	360 g