

Megapixel Classic IP Camera with Motor-zoom lens and Electronic Day/Night Function NVIP-2C5005CZ-P/GO



Features

- Electronic day/night function
- Imager: 3.0 MPX CMOS, 1/2.8" SONY
- Camera resolution: 2.0 MPX (Full HD)
- Min. Illumination: 0.63 lx/F=3.5
- Digital Slow Shutter (DSS)
- Digital Noise Reduction (DNR)
- Automatic Defective Pixel Correction (DPC)
- Motor-zoom lens 5x, AI and AF function: f=5 ~ 25 mm (F3.5 ~ F3.7)
- Built-in webserver: video compression and real-time network transmission
- Compression: H.264 or M-JPEG
- Video processing resolution: 1920 x 1080 Full HD
- Dual streaming: compression, resolution, speed and quality defined individually for two video streams
- RTP/RTSP protocol support for video transmission
- Hardware motion detection
- PoE (Power over Ethernet) support

Specifications	Description
Pick-up Element	1/2.8" SONY 3.0 MPX CMOS imager, progressive scanning
Camera Resolution	2.0 MPX (Full HD)
Min. Illumination	0.63 lx/F=3.5 - color mode 0.63 lx/F=3.5 - B/W mode
S/N Ratio	> 50 dB (AGC Off)
Electronic Shutter	Auto/Manual (1/4 ~ 1/2 000 s)
Digital Slow Shutter (DSS)	x2
White Balance	Manual/ATW
Day/Night Switching	Auto
Lens type	Motor-zoom lens 5x, AI and AF function: f=5~25 mm (F3,5~ F3,7)
Angle of View (H)	52° ~ 11°
Image Functions	Automatic DPC (Defective Pixel Correction)
Video Output	1.0 Vp-p/75 Ohm (BNC)
Video Compression	H.264/M-JPEG
Resolution	1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768, 704 x 576, 640 x 480, 352 x 288
System Reaction to Alarm Events	E-mail with attachment, saving file on FTP
Frame Rate	Up to 30 fps for 1920 x 1080 and lower resolution
Image Saving Files	JPEG
Video streaming	2 streams

Specifications	Description
External Ports	1 x Ethernet - RJ-45 connector, 10/100 Mbit/s
Motion Detection	Hardware
Time Synchronization	Automatic time synchronization with NTP server
Network Protocols Support	HTTP, TCP/IP, UDP, FTP, DHCP, NTP, RTSP, RTP, UPnP
User Authorization	Password protected camera access and its configuration
Power Supply	PoE (IEEE 802.3af)
Power Consumption	5.7 W
Operating Temperature	0°C ~ 40°C
Dimensions (mm)	62.8 (L) x 50.6 (W) x 47.4 (H)
Weight	160 g